

# Fitting Instructions #TRC4004 & TRC4007

## 10mm & 12mm Universal Sway Bar Link Kit

*For replacement of OE (Original Equipment) sway bar links or fitment with a replacement sway bar*



We recommend the below work be carried out by a licensed workshop or trades person, where a workshop manual and relevant safety procedures are followed:

- Ensure all sway bar link pins are in a neutral position for maximum operational articulation – refer images below.
- For vehicles with equal length OE links on each side, both sway bar links must also be of equal length to ensure ball ends are in a neutral position;
- If possible, set the adjustable sway bar links with the vehicle on all four wheels positioned at static ride height on a flat surface, then neutralise lengths. DO NOT Attempt to “preload” the sway bar, this may result in component failure;
- The sway bar link is designed to be the failsafe if incorrect adjustment occurs and this component will fail, instead of chassis or strut mountings.

### To Install:

- Remove the OE sway bar link pin assembly, following all workshop safety procedures.
- Measure the length of the OE link measuring from centre of ball end to centre of ball end, this is used as a baseline for the Universal link.
- Take note of the pin orientation, are they, in line, 180 degrees opposed, 90 degrees opposed etc. If unsure, refer images below of pin orientations.
- Using the diagram on the back of this page, cut the link to length using a hack-saw or grinder, ensure to have the lock nut in place during cutting to allow for a simple clean-up of threads. To do this simply unwind the locknut off the threaded rod and wind it back on.
- Apply a small volume of thread retaining compound, Loctite 243 or similar, to the threaded end and screw it into the Loose ball end, winding it all the way down till it stops, then unwinding to match the pin orientation to the OE part. Finally Tighten the lock nut to the ball end.
- Refit to vehicle, ensuring the ball ends are always in a neutral position to ensure maximum articulation;
- Tension ball end nuts (**refer table below**) with a torque wrench, after tensioning at least 2 threads should be seen past the nut:

	Torque settings
TRC4004 - 10mm Ball Joint Link (M10)	28Nm
TRC4007 - 12mm Ball Joint Link (M12)	44Nm

# Fitting Instructions #TRC4004



Bad Link Pin Angle

Neutral Link Pin Angle



180 Degree Opposed pins

90 Degree pins

Inline pins

- After Measuring the OE Pin to Pin Centreline length, the new universal fit link can be cut to length, measuring as shown diagram below mark the cut point;
- Cut the threaded section **20mm shorter than the OE Pin-to-Pin length**
- Using a Angle Grinder or Hacksaw, cut on the cut line. Ensure the Lock nut is threaded on the link, it is used to assist in deburring the threads by winding it off;
- The tolerance for this cut is +2mm -2mm I.e. If the Cutting length is 281mm, the actual cut length can be between 279mm and 283mm

