


Install Guide

Front Radius Arms

- Complete with new Bushings

This instruction sheet should be used in conjunction with the workshop manual and proper safety procedures followed.



Application - Suzuki Jimny

(Always refer complete catalogue listing)

Contents - 2x complete radius arms
- complete with installed bushings.
- off-set bushings supplied in rear bushing positions

- Raise vehicle evenly and safely support.

Never rely on a Jack only

IMPORTANT - Its is safest and easiest to replace 1 arm only at a time

Note - these arms offer off-set rear bushings. This offers the ability to tune front suspension for vehicles that may pull left or right - OR to simply increase wheel base both sides.


Lubricate all bolts prior to disassemble.

- Start by dis-connecting front lower shock mounts. The axle will have to be supported first.

It may be easiest to simply remove shock all together.

- Proceed to remove original arm - loosen and remove all 3 mounting bolts.

Refer Page 2



It is recommended that a licenced workshop or tradesperson carry out the above procedure and that workshop manual and relevant safety procedures are followed in addition to the above.


Install Guide Front Radius Arms - Complete with new Bushings

This instruction sheet should be used in conjunction with the workshop manual and proper safety procedures followed.

- Remove all 3 nuts from the 3 mounting points - then proceed to remove arm.

(Don't discard hardware)

- Grease bushings internal diameter and side face with supplied grease only.




- Note off-set tubes in rear mount point.

For ideal driving experience - refer diagram below

- Alternatively - determine if vehicle pulls left or right.

If vehicle pulls left - then the left arm must sit forward.

if vehicle doesn't pull, then there is the option to push both arms forward.



Refer Page 3

It is recommended that a licenced workshop or tradesperson carry out the above procedure and that workshop manual and relevant safety procedures are followed in addition to the above.

Install Guide

Front Radius Arms

- Complete with new Bushings

This instruction sheet should be used in conjunction with the workshop manual and proper safety procedures followed.

- Bolt up arms to vehicle with original bolts.
- Re-fit shocks.
- A wheel alignment is required immediately after install.
- Re-check all bolts after 200kms



It is recommended that a licenced workshop or tradesperson carry out the above procedure and that workshop manual and relevant safety procedures are followed in addition to the above.