

Instructions

Rear Diff - Rear Bushing

N.B: This instruction sheet should be used in conjunction with the workshop manual and proper safety procedures followed.

Page 1 of 2

Application - Mazda CX-5
- 2012 - on

(Refer current catalogue listing)

Contents - 1x bushing 91373

1. Raise vehicle evenly and safely support.
2. Un-bolt and remove rear muffler.
3. Using an Air-Hacksaw (or drill), cut one slot into the original outer steel shell.



Careful not to damage Sub-frame

4. The original bushing will contract.

Push bushing backwards with a hammer and steel punch.

5. Wipe Sub-frame Eye clean.

N.B: It is recommended that a licenced workshop or tradesperson carry out the above procedure and that workshop manual and relevant safety procedures are followed in addition to the above.

Instructions

Rear Diff - Rear Bushing

N.B: This instruction sheet should be used in conjunction with the workshop manual and proper safety procedures followed.

Page 2 of 2

Application - Mazda CX-5
- 2012 - on

(Refer current catalogue listing)

Contents - 1x bushing 91373

6. Push new supplied bushing in until it meets Differential bracket.



7. Re-use original washer and flange nut - tighten to 80 Nm.

8. Bolt up exhaust and road test.

N.B: It is recommended that a licenced workshop or tradesperson carry out the above procedure and that workshop manual and relevant safety procedures are followed in addition to the above.