



AC3011-24

This **Modular Air Control Kit** is a very convenient system easily added to existing air suspension products or as part of a full Airbag Man package.

What it does ? This system lets you inflate or deflate two air springs individually at the flick of a switch. It provides adjustment for up/down & side to side levelling & comes equipped with tyre inflation.



KIT INCLUDES:

AC8110-24 Air Compressor : High Quality 24V Heavy Duty Air Compressor, 200PSI Working Pressure, 50% Duty Cycle, 76 LPM / 2.70 CFM @ 0PSI, Max Amp Draw 18 Amps.

Compressor Dimensions : 220mm L x 115mm W x 175mm H
Space Required (open at one end for ventilation)
336mm L x 127mm W x 222mm H.

Control Panel : Dual Paddle Airbag Control Switches for Inflate & Deflate, Req. 22.5mm W x 40.6mm H Hole, Dual Switch Mounting Bracket Included & Tyre Inflation Wand 7.5 m / 25, Multi-Fit, Easy Install Panels.

Air Tank: 1 Gal / 4 L Seamless Lightweight Aluminium Air Tank SAE J10 Approved, No Corrosion, Max Working Pressure 200PSI Pressure Tested to 1000PSI, 3 x 1/4" NPT Ports Inc. Drain Port Multi-position Low Profile Bracket Set
Size: 605mm L x 100mm D x 126mm H (with mounting legs attached)

Fittings Kit : High Quality 1/4" nylon tubing, Quick fit push-to-connect air fittings, easy to use electrical connections, fuse & holder included.

*** Easy to Read Step By Step Instructions with Schematic Drawings Included in Every Kit.**

OPTIONAL GAUGE ADD-ONS



24V DUAL NEEDLE GAUGE

Dual Needle 24 Volt (Req. 52.5mm minimum hole)
Pressure Monitoring Gauge, 0-150PSI.

SKU AC3050-24

**Order individually or in conjunction with your Air Control or Supply System.*

*** Easy to Read Step By Step Instructions with Schematic Drawings Included in Every Kit.**